


Product Image



Product Dimensions



Characteristics

Nominal Voltage		12V
Nominal Capacity (10 hour rate)		105Ah
Capacity 25°C (77°F)	20 hour rate (5.82A)	116.5Ah
	5 hour rate (19.2A)	96Ah
	1 hour rate (69.8A)	69.8Ah
Internal Resistance	Full Charged Battery 25°C	≤5.0m Ω
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	0°C (32°F)	85%
	-15°C (5°F)	65%
Self-Discharge 25°C (77°F) Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 26.25A Voltage 13.6-13.8V
	Cycle	Initial Charging Current Less than 26.25 A Voltage 14.4-14.9V

Packaging

Battery Dimensions	Length	407mm
	Width	175mm
	Height	208mm
	Total Height	238mm
Box Dimensions	Length	422mm
	Width	188mm
	Height	290mm
Quantity Per Box		1 PC per box
Net weight Per Cell		31.2kg±400g
Net weight Per Box		31.2kg
Gross Weight		31.7kg

Discharge Constant Current per Cell (Amperes at 77°F25°C)







F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	303.5	195.1	162.5	108.4	77.7	67.0	29.6	28.9	19.6	12.9	11.6	6.1
1.65V	297.9	191.5	159.6	106.4	76.3	65.7	29.0	28.4	19.3	12.7	11.3	6.0
1.70V	292.4	188.0	156.6	104.4	74.9	64.6	28.5	27.8	18.9	12.5	11.1	5.9
1.75V	286.9	184.5	153.6	102.5	73.5	63.3	27.9	27.3	18.6	12.2	10.9	5.8
1.80V	275.8	177.3	147.7	98.5	70.7	60.9	26.9	26.3	17.9	11.8	10.5	5.6

Discharge Constant Power per Cell (Watts at 77°F 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	584.1	375.5	312.8	208.5	149.6	128.9	56.9	55.5	37.8	24.9	22.3	11.8
1.65V	573.5	368.7	307.1	204.8	146.9	126.6	55.9	54.6	37.1	24.5	21.8	11.6
1.70V	562.8	361.8	301.5	201.0	144.2	124.2	54.8	53.6	36.4	24.0	21.4	11.3
1.75V	552.2	355.0	295.8	197.2	141.4	121.9	53.9	52.6	35.7	23.5	21.0	11.1
1.80V	531.0	341.4	284.3	189.6	136.1	117.3	51.8	50.5	34.3	22.7	20.3	10.7

Note The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact **US** for the latest information.

Performance Characteristics



Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Lead	Fiberglass	Sulfuric acid

Guangdong JiYi General Electric Co., Ltd.

Oversea sales office Tel: +86-020-84869873 Fax: +86-020-34628335

Domestic sales office Tel: 020-34628335 Fax: 020-34628335

E-mail: ge@gerch.cn