


Product Image



Product Dimensions



Characteristics

Nominal Voltage		12V
Nominal Capacity (20 hour rate)		2.3Ah
Capacity 25°C (77°F)	10 hour rate (0.22A)	2.2Ah
	5 hour rate (0.41A)	2.05Ah
	1 hour rate (1.52A)	1.52Ah
Internal Resistance	Full Charged Battery 25°C	≤40m Ω
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	-20°C (-4°F)	82%
	-35°C (-31°F)	65%
Self-Discharge 25°C (77°F) Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 0.69A Voltage 13.6-13.8V
	Cycle	Initial Charging Current Less than 0.69A Voltage 14.4-15.0V

Packaging

Battery Dimensions	Length	177mm
	Width	35mm
	Height	61mm
	Total Height	67mm
Box Dimensions	Length	393mm
	Width	183mm
	Height	152mm
Quantity Per Box		20 PC per box
Net weight Per Cell		1kg±50g
Net weight Per Box		20kg
Gross Weight		20.5kg

Discharge Constant Current per Cell (Amperes at 77°F25°C)









F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	7.3	4.8	3.6	2.42	1.69	1.45	0.91	0.62	0.41	0.28	0.23	0.12
1.65V	7.1	4.8	3.6	2.38	1.66	1.43	0.89	0.61	0.41	0.27	0.23	0.12
1.70V	7.0	4.7	3.5	2.33	1.63	1.40	0.87	0.60	0.40	0.27	0.22	0.12
1.75V	6.9	4.6	3.4	2.29	1.60	1.37	0.86	0.59	0.39	0.26	0.22	0.11
1.80V	6.6	4.4	3.3	2.20	1.54	1.32	0.83	0.57	0.38	0.25	0.21	0.11

Discharge Constant Power per Cell (Watts at 77°F 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	14.0	9.3	7.0	4.66	3.26	2.80	1.75	1.20	0.80	0.54	0.44	0.23
1.65V	13.7	9.1	6.9	4.57	3.20	2.74	1.72	1.18	0.78	0.53	0.44	0.23
1.70V	13.5	9.0	6.8	4.49	3.14	2.69	1.68	1.15	0.77	0.52	0.43	0.22
1.75V	13.2	8.8	6.6	4.40	3.08	2.64	1.65	1.13	0.75	0.51	0.42	0.22
1.80V	12.7	8.5	6.4	4.24	2.96	2.54	1.59	1.09	0.73	0.49	0.40	0.21

Note The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact **US** for the latest information.

Performance Characteristics



Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Copper	Fiberglass	Nano

Guangdong JiYi General Electric Co., Ltd.

Oversea sales office Tel: +86-020-84869873

Fax: +86-020-34628335

Domestic sales office Tel: 020-34628335

Fax: 020-34628335

E-mail: ge@gerch.cn