


Product Image



Product Dimensions



Characteristics

Nominal Voltage		2V
Nominal Capacity (10 hour rate)		350Ah
Capacity 25°C (77°F)	20 hour rate (18.6A)	372Ah
	5 hour rate (61.8A)	309Ah
	1 hour rate (192.5A)	192.5Ah
Internal Resistance	Full Charged Battery 25 °C	≤0.45mΩ
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	0°C (32°F)	85%
	-15°C (5°F)	65%
Self-Discharge 25°C (77°F) Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 50A Voltage 2.23-2.27V
	Cycle	Initial Charging Current Less than 50A Voltage 2.33-2.37V

Packaging

Battery Dimensions	Length	172mm
	Width	150mm
	Height	330mm
	Total Height	365mm
Box Dimensions	Length	186mm
	Width	164mm
	Height	422mm
Quantity Per Box		1 PC per box
Net weight Per Cell		17.5 kg±200g
Net weight Per Box		18.0kg
Gross Weight		19kg

Discharge Constant Current (Amperes at 77°F25°C)







F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	1011.5	650.3	541.8	361.2	259.0	223.3	98.7	96.3	65.5	43.1	38.5	20.4
1.65V	993.0	638.4	532.0	354.6	254.5	219.1	96.6	94.5	64.4	42.4	37.8	20.0
1.70V	974.8	626.5	521.9	347.9	249.6	215.3	94.9	92.8	63.0	41.7	37.1	19.7
1.75V	956.2	615.0	512.1	341.6	245.0	211.1	93.1	91.0	62.0	40.6	36.4	19.3
1.80V	919.5	591.2	492.5	328.3	235.6	203.0	89.6	87.5	59.5	39.2	35.0	18.6

Discharge Constant Power (Watts at 77°F 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	1947.1	1251.6	1042.7	695.1	498.8	429.8	189.7	185.2	126.0	83.0	74.2	39.2
1.65V	1911.7	1228.9	1023.8	682.5	489.7	422.1	186.2	182.0	123.6	81.6	72.8	38.5
1.70V	1876.0	1206.1	1004.9	669.9	480.6	414.1	182.7	178.5	121.5	80.2	71.4	37.8
1.75V	1840.7	1183.4	986.0	657.3	471.5	406.4	179.6	175.4	119.0	78.4	70.0	37.1
1.80V	1770.0	1137.9	947.8	632.1	453.6	391.0	172.6	168.4	114.5	75.6	67.6	35.7

Note The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact **US** for the latest information.

Performance Characteristics



Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Lead	Fiberglass	Sulfuric acid

Guangdong JiYi General Electric Co., Ltd.

Oversea sales office Tel: +86-020-84869873

Fax: +86-020-34628335

Domestic sales office Tel: 020-34628335

Fax: 020-34628335

E-mail: ge@gerch.cn