


### Product Image



### Product Dimensions



### Characteristics

Nominal Voltage		6V
Nominal Capacity (20 hour rate)		4Ah
Capacity 25°C (77°F)	10 hour rate (0.38A)	3.83Ah
	5 hour rate (0.71A)	3.56Ah
	1 hour rate (2.64A)	2.64Ah
Internal Resistance	Full Charged Battery 25°C	≤18m Ω
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	-20°C (-4°F)	82%
Self-Discharge 25°C (77°F) Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 1.2A Voltage 6.8-6.9V
	Cycle	Initial Charging Current Less than 1.2A Voltage 7.2-7.5V

### Packaging

Battery Dimensions	Length	70mm
	Width	47mm
	Height	101mm
	Total Height	107mm
Box Dimensions	Length	305mm
	Width	260mm
	Height	122mm
Quantity Per Box		20 pcs per box
Net weight Per Cell		0.67 kg±50g
Net weight Per Box		13.4kg
Gross Weight		13.9kg

#### Discharge Constant Current per Cell (Amperes at 77°F 25°C)









F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	11.56	7.43	6.19	4.13	2.96	2.55	1.13	1.10	0.75	0.49	0.44	0.23
1.65V	11.35	7.30	6.08	4.05	2.91	2.50	1.10	1.08	0.74	0.48	0.43	0.23
1.70V	11.14	7.16	5.96	3.98	2.85	2.46	1.08	1.06	0.72	0.48	0.42	0.22
1.75V	10.93	7.03	5.85	3.90	2.80	2.41	1.06	1.04	0.71	0.46	0.42	0.22
1.80V	10.51	6.76	5.63	3.75	2.69	2.32	1.02	1.00	0.68	0.45	0.40	0.21

#### Discharge Constant Power per Cell (Watts at 77°F 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	22.25	14.30	11.92	7.94	5.70	4.91	2.17	2.12	1.44	0.95	0.85	0.45
1.65V	21.85	14.04	11.70	7.80	5.60	4.82	2.13	2.08	1.41	0.93	0.83	0.44
1.70V	21.44	13.78	11.48	7.66	5.49	4.73	2.09	2.04	1.39	0.92	0.82	0.43
1.75V	21.04	13.52	11.27	7.51	5.39	4.64	2.05	2.00	1.36	0.90	0.80	0.42
1.80V	20.23	13.00	10.83	7.22	5.18	4.47	1.97	1.92	1.31	0.86	0.77	0.41

**Note** The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact **US** for the latest information.

### Performance Characteristics



### Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Copper	Fiberglass	Nano

**Guangdong JiYi General Electric Co., Ltd.**

Overseas sales office Tel: +86-020-84869873

Fax: +86-020-34628335

Domestic sales office Tel: 020-34628335

Fax: 020-34628335

E-mail: ge@gerch.cn